

Exam Number/Code:BCP-520

Exam Name:Integrating the
BlackBerry MVS Solution

Version: Demo

<http://cert24.com/>

QUESTION NO: 1

What happens during an active BlackBerry MVS call when a failover is initiated by the BlackBerry MVS Console? (Choose one.)

- A. Active BlackBerry MVS Wi-Fi calls are preserved
- B. Active BlackBerry MVS Voice over Mobile calls are preserved
- C. All Active BlackBerry MVS calls are dropped without notification
- D. All Active BlackBerry MVS calls are preserved
- E. All Active BlackBerry MVS calls are dropped after the notification tone

Answer: D

QUESTION NO: 2

Which type of database authentication is required if BlackBerry MVS is installed on a different Microsoft Windows domain than the BlackBerry Enterprise Server? (Choose one.)

- A. Microsoft Windows authentication
- B. Microsoft SQL Server authentication
- C. Authentication set to db_owner
- D. Trusted authentication

Answer: B

QUESTION NO: 3

For BlackBerry devices that operate on GSM networks, which Voice over Mobile call direction offers optimal performance and reliability? (Choose one.)

- A. BlackBerry device-initiated
- B. SIP Line
- C. SIP Trunk
- D. PBX-initiated
- E. Voice over Wi-Fi

Answer: D

QUESTION NO: 4

What are three functions of the SIP Line connection between the BlackBerry MVS Session Manager and the PBX? (Choose three.)

- A. Registering BlackBerry MVS users with the PBX

- B. Communicating Call setup messages
- C. Reporting on the health of the BlackBerry MVS Session Manager
- D. Exchanging KPML messages
- E. Performing PBX directory lookups

Answer: A,B,D

QUESTION NO: 5

Which logging level in the BlackBerry Mobile Voice System Configuration tool logs the SIP messages between the BlackBerry MVS Server and PBX? (Choose one.)

- A. Info
- B. Severe
- C. Warning
- D. Finer
- E. Finest

Answer: E

QUESTION NO: 6

Which service book is required by the BlackBerry MVS Client to function properly? (Choose one.)

- A. Desktop [VoIP]
- B. Desktop [MVSSIP]
- C. Desktop [BBMVS]
- D. Desktop [BBSIP]

Answer: D

QUESTION NO: 7

What is the maximum round trip ping time supported between Cisco Unified Communications Manager and the BlackBerry MVS Session Manager? (Choose one.)

- A. 40 milliseconds
- B. 80 milliseconds
- C. 120 milliseconds
- D. 240 milliseconds
- E. 480 milliseconds

Answer: D

QUESTION NO: 8

What is the purpose of the line port in the BlackBerry MVS Telephony Connector configuration? (Choose one.)

- A. To allow the BlackBerry MVS Session Manager to receive BlackBerry-initiated calls from the SIP Line on the PBX
- B. To allow the BlackBerry MVS to forward calls using the SIP Line on the PBX to the mobile number of the BlackBerry device
- C. To allow BlackBerry MVS to initiate calls using the SIP Line on the PBX to the mobile number of the BlackBerry device
- D. To allow BlackBerry MVS Clients to register as a BlackBerry MVS Client on the PBX using the SIP Line

Answer: D

QUESTION NO: 9

What is the primary function of the BlackBerry Dispatcher in the BlackBerry MVS Solution? (Choose one.)

- A. It compresses and encrypts all data that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the BlackBerry Router to the BlackBerry MVS Session Manager.
- B. It compresses and encrypts all data that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the BlackBerry Router, to and from the wireless network.
- C. It compresses and encrypts all data that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the media gateway, to and from the wireless network.
- D. It compresses and encrypts RTP traffic that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the media gateway, to and from the wireless network.
- E. It compresses and encrypts RTP traffic that BlackBerry devices send and receive. The BlackBerry Dispatcher sends the data through the BlackBerry Router, to and from the wireless network.

Answer: B

QUESTION NO: 10

An organization has a hunt group that is configured in the PBX with multiple outgoing trunks. Each trunk is assigned a unique Caller Identification Number. Where must each

Caller Identification Number be added to ensure that PBX-initiated calling will work?
(Choose one.)

- A. The MVS locations field in the BlackBerry MVS Console
- B. The BlackBerry MVS Client on the BlackBerry device
- C. The BlackBerry MVS Session Manager in the BlackBerry MVS Console
- D. The BlackBerry MVS Telephony Connector in the BlackBerry MVS Console

Answer: D